

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 153 708 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

14.11.2001 Bulletin 2001/46

(51) Int Cl.7: **B23Q 11/10**

(21) Application number: **01304061.3**

(22) Date of filing: **03.05.2001**

(84) Designated Contracting States:

**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**

Designated Extension States:

AL LT LV MK RO SI

• **Hill, Christopher Peter Ralph**

Thornbury, Bristol BS35 1HX (GB)

• **Watkins, James Rodney**

Stoke Bishop, Bristol BS34 6BS (GB)

(30) Priority: **11.05.2000 GB 0011315**

(71) Applicant: **ROLLS-ROYCE plc**

London, SW1E 6AT (GB)

(74) Representative: **Bird, Vivian John**

Rolls-Royce plc,

Intellectual Property Department,

P.O. Box 3,

EW 1-5

Filton, Bristol BS34 7QE (GB)

(72) Inventors:

• **Church, Richard**

Knowle, Bristol BS14 9ED (GB)

(54) **High speed milling**

(57) A method of high speed milling, and apparatus for performing the method, comprises directing a jet of high pressure coolant at the cutting zone of a rotary cutting tool. The jet of coolant has a delivery pressure of

up to 500 bar at a flow rate of up to 60 litres per minute. The method is especially effective when used with a rotary cutting tool having at least 20 cutting edges and up to 100 cutting edges.

EP 1 153 708 A1

Description

[0001] The invention relates to a method and apparatus for high speed milling.

[0002] A method for the controlled removal of chips in boring mills is described in European Patent Application No 0,624,429. According to this method, and in the boring mill apparatus constructed in accordance with the principles of the method, one or more jets of fluid at high pressure is directed at the location where chips tend to accumulate. The cutting fluid is drawn from a reservoir by a pump capable of operating at 130-200 bar with a flow rate or the order of approximately 30 litres per minute, and is directed at the chips emerging from the cutting to promote their natural removal. The purpose of the jets is to cause the chips to break off quickly and to clear away the chips instead of allowing them to accumulate in the region of the cutting.

[0003] The boring mill described is arranged vertically with the cutting tool and fluid jets suspended below an overhead portion of the machine with the workpiece mounted below. The chips naturally tend to fall downwards when broken-off by the jets because of their weight. The cutting tool and the fluid nozzles are held stationary relative to the fixed part of the boring mill while the workpiece is rotated about the vertical axis to generate the cutting movement. This kind of arrangement is suitable for boring cylindrical surfaces and at relatively low shock removal rates with single point cutting tools, but does not lend itself to use with high speed rotary cutting tools of the type used in conjunction with multi-axis machining centres.

[0004] According to one aspect the invention concerns improvements to a milling operation employing a milling cutter of the kind described in our co-pending application entitled "Multi-Fluted Milling Cutter", GB Patent Application No 0011215.1 (priority application). According to another aspect of the invention the improvements concern modifications to apparatus for performing the milling operation.

[0005] According to the present invention in its broadest aspect a method of high speed milling a method of high speed milling using a rotary cutting tool including the step of directing towards the cutting zone of the rotary cutting tool a jet of high pressure coolant delivered at a pressure of at least 5 Bar and up to about 500 Bar.

[0006] Also according to the invention there is provided apparatus for carrying out the method of high speed milling as claimed in any preceding claim comprising a spindle for mounting a rotary cutting tool, at least one nozzle for directing towards the cutting zone of the rotary cutting tool a jet of high pressure coolant, a source of high pressure coolant connected with said nozzle to deliver a jet of high pressure coolant of at least 5 Bar and up to about 500 Bar.

[0007] The invention and how it may be carried into practice will now be described in more detail with reference to an arrangement illustrated in the accompanying

drawing.

[0008] The illustration of a high speed milling arrangement shows a rotary cutting tool in the form of a multi-fluted milling cutter 2, which may be of the kind referred to above, carried in a tool holder 4 mounted on the rotating spindle 6 of a multi-axis machining centre. The spindle axis of the machine may be horizontal as illustrated in the drawing. The workpiece to be milled is shown at 5 mounted on a multi-axis worktable, shown at 7, of a conventional kind.

[0009] A coolant nozzle 8 is aimed at the cutting zone of the milling cutter 2. Coolant is supplied to nozzle 8 from a fluid source (not shown) through supply ducting comprising pipes 10, 12. Supply pipe 12 is rotatably mounted in a swivel coupling 14 which allows pipe 12 to be rotated about its longitudinal axis 16. By swivelling the pipe 12 about its axis the pipe 10 and nozzle 8 may be swung away from the vicinity of the milling cutter 2 thereby providing sufficient clearance for an automatic tool change mechanism to operate to remove and replace the mill 2 and tool holder 4. The swivel coupling 14 is arranged to receive a supply of liquid coolant through a further static pipe 18 connected to source of high pressure coolant (not shown). The coupling 14 is arranged internally to convey the supply of coolant from static pipe 18 to rotatable pipe 12 with minimal loss of pressure and, failures aside, without leakage. In the context of the present invention high pressure coolant refers to coolant delivered at a pressure in the range from about 40 Bar to about 70 Bar but may be up to 500 Bar, and at a flow rate of up to 60 litre per minute or greater.

[0010] The coolant nozzle 8 is adapted and arranged to direct the jet of high pressure coolant, issuing from it in use, substantially in the direction of the flutes towards the cutting zone of the rotary cutting tool 2. The high pressure coolant jet assists chip evacuation and is preferably delivered at a pressure of at least 5 Bar and, as mentioned, at up to a pressure within the range from about 40 Bar to about 70 Bar. Preferably the milling cutter is of the kind described in our co-pending patent application referenced above, and has a multiplicity of small helical flutes or cutting edges at about 20 or 25 in number and possibly up to about 100 or even more.

[0011] The invention may be applied to all geometries of milling cutter and to shallow drilling. The effect of the relatively fixed high pressure jet of coolant directed into the cutting zone of the rotary cutting tool gives very effective swarf removal so that the milling or drilling tool may be provided with smaller flutes and hence stronger cutting teeth. Tool wear is also reduced and, in turn, tool rotational speed may be increased and overall material removal rates may be substantially higher than hitherto achieved. The method may be carried into practice using a multi-axis, numerically controlled machining centre. Such machines usually have a horizontal spindle and a high flow rate, but low pressure, coolant delivery system which fairly well floods the region of the work-

piece being machined. In carrying out the present invention it is envisioned that the high pressure coolant delivery nozzles will be used close to the rotary cutting tool in conjunction with the usual low pressure coolant system which carries away machining debris.


5

12. Apparatus substantially as hereinbefore described for carrying out a method of high speed milling in accordance with any one of claims 1 to 6.

Claims

1. A method of high speed milling using a rotary cutting tool including the step of directing towards the cutting zone of the rotary cutting tool a jet of high pressure coolant delivered at a pressure of at least 5 Bar and up to about 500 Bar. 10
2. A method as claimed in claim 1 wherein the jet of high pressure coolant is delivered at a pressure within the range of about 40 Bar up to about 70 Bar. 15
3. A method as claimed in either claim 1 or claim 2 wherein the jet of high pressure coolant is delivered at a flow rate of up to 60 litres per minute or greater. 20
4. A method as claimed in any preceding claim wherein the rotary cutting tool comprises a multi-flute milling cutter having at least 20 cutting edges. 25
5. A method as claimed in claim 4 wherein the rotary cutting tool has up to about 100 cutting edges. 30
6. A method of high speed milling substantially as hereinbefore described. 30
7. Apparatus for carrying out the method of high speed milling as claimed in any preceding claim comprising a spindle for mounting a rotary cutting tool, at least one nozzle for directing towards the cutting zone of the rotary cutting tool a jet of high pressure coolant, a source of high pressure coolant connected with said nozzle to deliver a jet of high pressure coolant of at least 5 Bar and up to about 500 Bar. 35 40
8. Apparatus as claimed in claim 7 wherein the rotary cutting tool has up to about 100 cutting edges. 45
9. Apparatus as claimed in claim 7 or claim 8 comprising a horizontal spindle, multi-axis machining centre. 45
10. Apparatus as claimed in any one of claims 7, 8 or 9 further comprising nozzle mounting means arranged for movement concentric with the spindle axis of the machining centre. 50
11. Apparatus as claimed in claim 10 wherein the nozzle mounting means is arranged to swing clear of the machine spindle for a tool changing operation. 55

BEST AVAILABLE COPY





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 30 4061

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	PATENT ABSTRACTS OF JAPAN vol. 016, no. 187 (M-1244), 7 May 1992 (1992-05-07) -& JP 04 025309 A (GENICHI SATO), 29 January 1992 (1992-01-29)	1,3,6-9, 12	B23Q11/10
Y	* abstract *	4	
A	* figures *	2	
X	EP 0 579 371 A (MAKINO MILLING MACHINE) 19 January 1994 (1994-01-19)	1-3,6,7, 9,12	
A	* column 2, line 44 - line 54 * * column 3, line 53 - column 4, line 4 * * column 8, line 43 - column 9, line 21 * * column 10, line 57 - column 11, line 14 * * figures 1,6,8A,8B *	4,8	
X	EP 0 924 028 A (ROLLS ROYCE PLC) 23 June 1999 (1999-06-23)	7,9-11	
A	* column 1, line 58 - column 2, line 11 * * column 3, line 20 - line 28 * * column 5, line 4 - column 7, line 25 * * claims 3,6,7 * * figure 2 *	1-3	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			B23Q
X	US 2 653 517 A (PIGOTT REGINALD J S) 29 September 1953 (1953-09-29)	1,3,7	
	* column 5, line 75 - column 6, line 9 * * column 6, line 65 - line 73 * * figures 8,9 *		
X	EP 0 911 113 A (ENSHU LIMITED) 28 April 1999 (1999-04-28)	1,3,7	
	* column 6, line 2 - line 33 * * figures 1,17A *		
	-/--		
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 9 August 2001	Examiner Breare, D
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons</p> <p>& : member of the same patent family, corresponding document</p>			



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 30 4061

DOCUMENTS CONSIDERED TO BE RELEVANT				
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)	
X	EP 0 123 387 A (YANKOFF GERALD K) 31 October 1984 (1984-10-31) * page 10, line 1 - line 7 * * page 12A, line 1 - line 5 * * page 16, line 21 - page 17, line 5 * * page 18, line 12 - line 22 * * page 33, line 24 - page 34, line 4 *	1,3		
X A	US 5 148 728 A (MAZURKIEWICZ MARIAN) 22 September 1992 (1992-09-22) * column 1, line 32 - line 45 * * column 2, line 39 - line 43 * * column 5, line 64 - column 6, line 2 * * figures 1,4 *	1,3 7		
Y	"Fineline Tungsten-Carbide Burrs" MACHINERY, vol. 102, no. 2638, 5 June 1963 (1963-06-05), page 1296 XP002173557	4		
A	* the whole document *	5,8		TECHNICAL FIELDS SEARCHED (Int.Cl.7)
A	WO 99 39852 A (LAGERBERG STIG ;SANDVIK AB (SE)) 12 August 1999 (1999-08-12) * page 2, line 1 - line 11 *	2,3,7		
A	US 5 718 156 A (LEBOULANGER JEAN-PIERRE ET AL) 17 February 1998 (1998-02-17) * column 1, line 40 - line 55 *	2,3,7		
The present search report has been drawn up for all claims				
Place of search THE HAGUE		Date of completion of the search 9 August 2001	Examiner Breare, D	
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons</p> <p>§ : member of the same patent family, corresponding document</p>				

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 4061

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

09-08-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 04025309 A	29-01-1992	NONE	
EP 0579371 A	19-01-1994	JP 2511368 B	26-06-1996
		JP 6134647 A	17-05-1994
		DE 69326397 D	21-10-1999
		DE 69326397 T	11-05-2000
		US 5378091 A	03-01-1995
		JP 10225814 A	25-08-1998
		JP 2894924 B	24-05-1999
		JP 6134648 A	17-05-1994
EP 0924028 A	23-06-1999	GB 2332634 A,B	30-06-1999
		JP 11254324 A	21-09-1999
		US 6123606 A	26-09-2000
US 2653517 A	29-09-1953	BE 509890 A	
		CH 303358 A	30-11-1954
		DE 930790 C	
		FR 1052110 A	21-01-1954
		GB 726183 A	16-03-1955
		LU 31452 A	
		NL 85277 C	
		NL 169522 B	
EP 0911113 A	28-04-1999	JP 11320328 A	24-11-1999
		JP 2000044209 A	15-02-2000
		JP 11197988 A	27-07-1999
		US 6200198 B	13-03-2001
		EP 0958887 A	24-11-1999
		US 6135862 A	24-10-2000
EP 0123387 A	31-10-1984	AU 2690984 A	10-09-1984
		DE 3466765 D	19-11-1987
		FI 844105 A	18-10-1984
		JP 60500607 T	02-05-1985
		NO 844260 A	25-10-1984
		WO 8403239 A	30-08-1984
		US 4621547 A	11-11-1986
		ES 532672 D	01-04-1985
		ES 8503992 A	01-07-1985
		NZ 207661 A	20-02-1987
		PT 78562 A,B	01-06-1984
		ZA 8403865 A	24-12-1984
US 5148728 A	22-09-1992	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 4061

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

09-08-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9939852 A	12-08-1999	SE 513480 C	18-09-2000
		EP 1073535 A	07-02-2001
		SE 9800212 A	28-07-1999
US 5718156 A	17-02-1998	FR 2713117 A	09-06-1995
		DE 69422599 D	17-02-2000
		DE 69422599 T	06-07-2000
		EP 0656239 A	07-06-1995
		ES 2140516 T	01-03-2000
		GR 3032985 T	31-07-2000
		IL 111803 A	17-08-1999
		JP 7185991 A	25-07-1995